

Full load performance calculated according to UNI EN 14511-2

KITA SP-8								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	3,41	2,19	3,17	1,82	3,02	1,55	2,77	1,31
-20	4,03	2,55	3,76	2,13	3,63	1,83	3,35	1,56
-15	4,59	3,01	4,41	2,45	4,16	2,13	3,92	1,78
-10	5,41	3,33	5,10	2,80	4,82	2,37	4,51	2,00
-7	5,76	3,72	5,53	3,00	5,23	2,54	4,87	2,14
2	7,01	4,92	6,62	3,96	6,29	3,32	5,71	2,70
7	8,00	5,78	7,51	4,55	7,12	3,70	6,41	3,00
12	9,00	6,91	8,49	5,24	7,98	4,19	7,18	3,35

KITA SP-10								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	4,37	2,12	4,12	1,79	4,02	1,53	3,73	1,33
-20	5,13	2,44	4,87	2,07	4,74	1,76	4,44	1,54
-15	5,87	2,86	5,67	2,36	5,51	2,00	5,14	1,73
-10	6,88	3,20	6,54	2,67	6,34	2,26	5,87	1,93
-7	7,36	3,52	7,09	2,87	6,87	2,42	6,35	2,05
2	8,81	4,72	8,45	3,76	8,08	3,17	7,42	2,60
7	10,00	5,44	9,56	4,27	9,13	3,53	8,33	2,87
12	11,30	6,37	10,77	4,90	10,24	4,02	9,33	3,21

KITA SP-12								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	6,49	1,93	6,31	1,62	6,13	1,39	5,90	1,21
-20	7,61	2,20	7,37	1,83	7,12	1,57	6,85	1,35
-15	8,82	2,50	8,53	2,06	8,20	1,75	7,82	1,49
-10	10,12	2,82	9,76	2,31	9,36	1,94	8,88	1,64
-7	10,94	3,02	10,55	2,46	10,09	2,06	9,55	1,73
2	11,53	4,23	11,04	3,39	10,47	2,80	9,78	2,32
7	12,10	4,99	11,56	3,95	10,93	3,23	10,15	2,66
12	13,65	5,81	13,01	4,51	12,28	3,65	11,38	2,97

Full load performance calculated according to UNI EN 14511-2

KITA MP-14								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	6,04	1,97	5,86	1,57	5,67	1,36	5,41	1,18
-20	7,10	2,27	6,89	1,80	6,65	1,55	6,35	1,34
-15	8,26	2,59	8,01	2,04	7,71	1,75	7,29	1,50
-10	9,52	2,95	9,22	2,31	8,84	1,96	8,32	1,66
-7	10,31	3,18	10,00	2,48	9,56	2,10	8,97	1,76
2	12,31	4,26	11,84	3,24	11,15	2,80	10,47	2,23
7	14,00	4,92	13,32	3,86	12,64	3,16	11,68	2,55
12	15,75	5,78	15,00	4,44	14,13	3,55	13,08	2,86

KITA MP-16								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	6,68	1,93	6,50	1,53	6,29	1,40	6,02	1,15
-20	7,84	2,21	7,62	1,74	7,35	1,50	7,04	1,29
-15	9,13	2,53	8,85	1,97	8,45	1,77	8,06	1,43
-10	10,49	2,88	10,17	2,22	9,68	1,98	9,18	1,59
-7	11,36	2,95	11,00	2,38	10,45	2,11	9,89	1,68
2	13,58	4,16	13,03	3,11	12,29	2,70	11,52	2,11
7	15,04	4,75	14,63	3,70	13,87	3,00	12,84	2,44
12	17,34	5,62	16,46	4,24	15,57	3,42	14,40	2,69

KITA MP-18								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	7,77	1,98	7,56	1,63	7,39	1,36	0,00	0,00
-20	9,17	2,32	8,94	1,92	8,72	1,60	8,52	1,35
-15	10,65	2,69	10,40	2,22	10,14	1,86	9,86	1,56
-10	12,23	3,07	11,93	2,53	11,62	2,12	11,25	1,77
-7	13,24	3,31	12,90	2,73	12,54	2,28	12,12	1,91
2	15,91	4,46	15,40	3,63	14,84	3,01	14,18	2,49
7	18,04	5,09	17,41	4,10	16,72	3,38	15,90	2,79
12	20,33	5,84	19,59	4,66	18,72	3,83	17,79	3,14

Full load performance calculated according to UNI EN 14511-2

KITA MP-20								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	9,84	1,94	9,61	1,59	9,44	1,34	0,00	0,00
-20	11,49	2,25	11,24	1,85	10,99	1,55	9,21	1,34
-15	13,25	2,58	12,94	2,12	12,64	1,77	12,30	1,49
-10	15,14	2,93	14,77	2,40	14,36	2,00	13,92	1,68
-7	16,38	3,16	15,91	2,57	15,47	2,15	14,94	1,80
2	18,42	4,27	17,80	3,46	17,15	2,87	16,38	2,37
7	20,00	4,90	19,25	3,96	18,49	3,26	17,60	2,70
12	22,47	5,63	21,63	4,51	20,74	3,70	19,69	3,04

KITA LP-22								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	10,04	1,87	9,76	1,54	9,55	1,30	0,00	0,00
-20	11,79	2,18	11,45	1,79	11,16	1,51	9,65	1,29
-15	12,87	2,51	13,25	2,06	12,16	1,73	12,44	1,45
-10	15,64	2,86	14,87	2,34	14,42	1,96	13,86	1,63
-7	16,10	3,08	15,59	2,51	14,95	2,11	14,48	1,75
2	20,20	4,09	19,41	3,30	18,63	2,75	17,69	2,27
7	22,00	4,52	21,97	3,72	20,97	3,01	19,88	2,53
12	22,92	5,41	24,72	4,29	23,61	3,54	22,24	2,88

KITA LP-26								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	12,01	2,11	11,82	1,72	11,69	1,44	11,53	1,21
-20	13,88	2,42	13,64	1,99	13,46	1,66	13,29	1,40
-15	15,88	2,76	15,60	2,26	15,35	1,90	15,11	1,60
-10	18,00	3,12	17,67	2,55	17,35	2,14	17,02	1,80
-7	19,44	3,35	19,02	2,74	18,61	2,29	18,23	1,93
2	23,12	4,44	22,53	3,61	21,94	3,02	21,09	2,54
7	26,18	5,08	25,46	4,10	24,73	3,41	23,92	2,86
12	29,54	5,81	28,69	4,65	27,82	3,87	26,84	3,23

Full load performance calculated according to UNI EN 14511-2

KITA LP-28								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	13,00	2,09	12,84	1,70	12,73	1,42	12,61	1,20
-20	14,98	2,40	14,77	1,96	14,60	1,64	14,45	1,38
-15	17,09	2,72	16,83	2,22	16,59	1,86	16,35	1,57
-10	19,35	3,06	19,02	2,50	18,70	2,09	18,37	1,77
-7	20,89	3,29	20,47	2,68	20,03	2,23	19,65	1,89
2	24,82	4,37	24,21	3,54	23,60	2,96	22,91	2,49
7	28,11	4,97	27,35	4,01	26,59	3,34	25,73	2,80
12	31,70	5,67	30,79	4,54	29,88	3,77	28,84	3,15

KITA LP-32								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	15,04	2,02	14,88	1,64	14,78	1,38	14,65	1,16
-20	17,32	2,31	17,09	1,88	16,89	1,57	16,70	1,33
-15	19,74	2,61	19,43	2,13	19,13	1,78	18,85	1,51
-10	22,33	2,93	21,93	2,38	21,55	2,00	21,14	1,70
-7	24,06	3,14	23,54	2,56	23,10	2,14	22,61	1,82
2	28,58	4,19	27,82	3,38	27,07	2,82	26,23	2,37
7	32,22	4,78	31,30	3,85	30,38	3,19	29,35	2,68
12	36,22	5,46	35,11	4,35	34,02	3,60	32,80	3,01

KITA LP-35								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	16,55	2,00	16,44	1,62	16,39	1,35	16,40	1,15
-20	18,97	2,27	18,79	1,84	18,61	1,54	18,44	1,30
-15	21,56	2,56	21,27	2,07	21,01	1,73	20,72	1,47
-10	24,36	2,87	23,97	2,32	23,59	1,95	23,16	1,65
-7	26,27	3,09	25,74	2,49	25,24	2,08	24,73	1,76
2	31,14	4,10	30,32	3,29	29,51	2,73	28,61	2,30
7	35,00	4,65	34,13	3,71	33,13	3,07	32,01	2,58
12	39,42	5,28	38,23	4,19	37,05	3,47	35,72	2,88

Full load performance calculated according to UNI EN 14511-2

KITA LP-PLUS-35								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	15,65	2,08	15,25	1,72	14,81	1,45	14,20	1,22
-20	17,96	2,33	17,53	1,93	17,08	1,64	16,54	1,39
-15	20,56	2,61	20,11	2,17	19,61	1,85	19,01	1,58
-10	23,46	2,95	22,94	2,44	22,36	2,07	21,67	1,77
-7	25,60	3,19	24,76	2,62	24,12	2,22	23,36	1,90
2	30,65	4,28	29,73	3,47	28,76	2,92	27,68	2,48
7	35,00	4,92	33,79	3,94	33,62	3,30	31,31	2,79
12	39,55	5,72	38,14	4,52	36,75	3,73	35,17	3,13

KITA LP-PLUS-40								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	18,03	2,04	17,69	1,69	17,28	1,43	16,75	1,22
-20	20,73	2,26	20,32	1,88	19,83	1,60	19,27	1,37
-15	23,72	2,52	23,22	2,10	22,68	1,79	22,04	1,53
-10	27,05	2,83	26,45	2,34	25,79	1,99	25,03	1,70
-7	29,34	3,04	28,59	2,51	28,04	2,23	26,93	1,81
2	35,35	4,07	34,28	3,31	33,18	2,78	31,93	2,35
7	40,00	4,72	38,98	3,75	37,50	3,12	36,11	2,64
12	45,62	5,44	44,14	4,27	42,51	3,52	40,67	2,95

Full load performance calculated according to UNI EN 14511-2

KITA LR-35								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	20,32	2,33	19,09	1,98	-	-	-	-
-20	22,89	2,58	20,41	2,10	19,72	1,82	-	-
-15	25,31	2,85	24,62	2,24	22,63	1,89	-	-
-10	28,04	3,08	27,37	2,47	26,86	2,02	-	-
-7	28,76	3,17	28,10	2,67	27,38	2,23	-	-
2	33,17	3,94	32,99	3,27	32,80	2,71	-	-
7	34,80	4,50	34,90	3,70	34,84	3,04	-	-
12	39,15	5,06	38,64	4,15	38,53	3,39	-	-

KITA LR-35 COLD								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	22,43	2,22	22,18	1,86	-	-	-	-
-20	24,93	2,42	24,45	2,03	22,95	1,84	-	-
-15	27,70	2,65	27,49	2,20	27,12	1,89	-	-
-10	30,69	2,91	30,49	2,43	29,82	2,08	-	-
-7	33,11	3,10	32,49	2,59	31,68	2,21	-	-
2	36,34	3,93	36,18	3,23	35,51	3,12	-	-
7	35,42	4,62	34,90	3,70	34,81	3,12	-	-
12	39,31	5,20	38,79	4,22	38,50	3,48	-	-

KITA LR-PLUS-45								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	27,63	2,31	27,62	1,87	-	-	-	-
-20	31,05	2,53	30,70	1,98	30,24	1,57	-	-
-15	34,69	2,83	34,02	2,20	33,24	1,74	-	-
-10	39,08	3,12	38,00	2,41	36,79	1,90	-	-
-7	41,95	3,37	40,64	2,60	39,20	2,04	-	-
2	45,59	4,01	44,14	3,10	42,55	2,43	-	-
7	48,67	4,58	46,89	3,52	44,97	2,75	-	-
12	51,00	5,02	48,89	4,02	46,75	2,94	-	-

Full load performance calculated according to UNI EN 14511-2

KITA HRP-10								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	4,42	2,00	4,24	1,67	4,06	1,43	3,87	1,23
-20	5,18	2,31	4,99	1,91	4,78	1,63	4,57	1,41
-15	6,02	2,64	5,81	2,18	5,55	1,86	5,28	1,59
-10	6,93	3,01	6,69	2,47	6,38	2,09	6,03	1,77
-7	7,50	3,25	7,24	2,66	6,90	2,23	6,50	1,88
2	9,06	4,43	8,69	3,53	8,20	2,89	7,64	2,40
7	10,32	5,16	9,87	4,04	9,30	3,25	8,62	2,67
12	11,69	6,07	11,17	4,66	10,50	3,70	9,68	2,98

KITA HRP-12								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	5,22	1,94	5,04	1,62	4,87	1,39	4,67	1,12
-20	6,11	2,23	5,90	1,85	5,69	1,58	5,46	1,36
-15	7,09	2,54	6,86	2,11	6,58	1,77	6,28	1,52
-10	8,13	2,88	7,85	2,37	7,54	1,99	7,14	1,69
-7	8,80	3,11	8,50	2,54	8,14	2,12	7,70	1,79
2	10,63	4,23	10,20	3,37	9,67	2,75	9,04	2,27
7	12,09	4,90	11,59	3,84	10,95	3,08	10,19	2,52
12	13,69	5,71	13,10	4,41	12,35	3,49	11,45	2,81

KITA HRP-14								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	6,13	1,86	5,96	1,55	5,79	1,33	5,61	1,16
-20	7,18	2,13	6,96	1,77	6,73	1,50	6,48	1,29
-15	8,30	2,42	8,06	1,99	7,76	1,67	7,41	1,43
-10	9,52	2,74	9,21	2,23	8,84	1,86	8,42	1,57
-7	10,31	2,96	9,94	2,39	9,54	1,98	9,04	1,66
2	12,42	3,99	11,97	3,18	11,33	2,57	10,60	2,11
7	14,09	4,61	13,51	3,60	12,78	2,87	11,93	2,33
12	15,93	5,34	15,25	4,12	14,39	3,23	13,39	2,60

Full load performance calculated according to UNI EN 14511-2

KITA HRP-16								
	W 35		W 45		W 55		W 65	
	P [kW]	COP	P [kW]	COP	P [kW]	COP	P [kW]	COP
-25	6,56	1,84	6,21	1,53	6,04	1,31	5,85	1,14
-20	7,67	2,10	7,23	1,74	7,00	1,47	6,75	1,27
-15	8,86	2,38	8,36	1,96	8,06	1,64	7,71	1,40
-10	10,15	2,70	9,56	2,20	9,18	1,83	8,74	1,54
-7	11,01	2,91	10,31	2,35	9,89	1,94	9,39	1,63
2	14,04	3,70	12,49	2,93	11,86	2,37	11,11	1,94
7	15,93	4,25	14,15	3,33	13,38	2,65	12,49	2,15
12	17,99	4,93	15,95	3,80	15,05	2,97	14,01	2,39